

SaffeGard Q-12WP

Wireless Door Entry Intercom

Operating Features

Basic Features

Wireless Doorphone-to-handset intercom.
Wirefree connection between Doorphone and Handset based on Powerline transmission.
Entry Doorphone directly pluggable into or connectable to nearby power receptacle.
Nearly Plug and Play install with yet a sophisticated Entry Panel.
Door release control with (1) form C relay.
Built-in power supply for door relay circuit.
Power line feed for immunity to battery wear, leak, weather breakdown and periodic change.

Advanced Features

Secured transceiver link between Entry Panel and Handsets.
Virtually no transmission range limitation as long as entry power outlet is on same electrical circuit as rest of premise.
Up to 16 indoor handsets each with own transceiver.
Built-in Port for Request-to-exit Button from inside property.
Audio monitoring capability.
Pluggable into a CO line port of a multi-line phone or a phone system in order to expand user base.

Optional Features

Radio wireless video with built-in camera within Entry Doorphone and mini LCD Screen.
For video reception choice of 7" LCD Screen, mini 2" portable LCD Screen and/or existing TV set.
Range of radio wireless video: 300ft line of sight between Entry Doorphone and indoor Screen.
Wireless Doorchime Kit for ringing an inside Doorchime box.
Available in Polished Brass, Brushed Stainless Steel, Black Powder Coat and Combo finishes.
Gooseneck mountable.

Installation & Interoperability

Test Kit to support easy installation.
Compatible with any telephone set.
Directly compatible with conventional PBX business phone systems.
Compatible with IP-based phone systems via ATA adaptor.
Compatible with Ennovah systems via WDA-2 Adaptor for enhanced integration with telephones.



Technical Specifications

Preset Power Source:
115VAC ~ 50/60 Hz ~ 50mA
or 230VAC ~ 50/60 Hz ~ 50mA
Built-in power supply: 18VAC
Weight: 9 lbs.
Operating Environment: 10° F - 95° F
Intercom Mode: Full-Duplex
Ring Generator: 7 REN maximum
Doorstrike Relay contact rating:
5A @ 24V DC or AC
Size of Enclosure: W 5.75 in x H 5.75 in
x D (bottom) 3.62 in x D (top) 3.75 in.
Size of Handles: W 3.5 X H 1 in.
Product code: Q-12WP