

# Ultimatoll Standard Q-16S-S

## Home Telephone Intercom System



### Operating Features

#### Standard Features

- Door-to-handset intercom with standard phone handsets.
- Door release from phone keypads with built-in electric keylock controller.
- Room-to-room intercom with standard handsets.
- Distinctive Page on intercom calls.
- Intercom running on existing phone wirelines with daisy-chain or home run wiring.
- Call waiting at door call while phone conversation ongoing.
- Call waiting at incoming phone call during entry intercom conversation.
- Full caller ID pass-thru to handsets.
- Installable by homeowner with minor tooling.

#### Advanced Features

- Yard monitoring from all doorphones simultaneously.
- Alarm surveillance with all-phone-ring alert or call directed to external phone number.
- Built-in programmable dial out to external phone number on doorphone calls.
- Room monitoring via home phones: one-to-one, one-to-many, many-to-many.
- Automatic call pick up and automatic hangup with speakerphones.
- Automatic busy redial from any extension phone.
- Screened call transfer or direct call transfer.
- Call parking with timeout alert.
- Barge-in over busy extension with privacy from remote line party.
- Three-party conference calls between two household users and one line party.
- Three-party conference calls between three household users.
- Integrates with answering machines for professional voice mail processing
- Toll restriction with password-protected override.
- Call recording with on-line activation/deactivation.
- Music on hold or personalized message from any sound appliance.
- Straightforward programming with standard phones.
- Emergency mode on power failure and more...

#### Optional Features

- Large variety of doorphone models: from standard plastic enclosure to vandal-proof metal doorphones.
- Video-enabled doorphones for video monitoring (concealed miniature camera within).
- Wholehouse voice page and music sub-system.
- Interoperable with existing wholehouse PA system.
- Interoperable with multi-unit dwelling intercom system.
- Upgradable to internet-friendly Premium System.
- And a whole lot more...

### Specifications

Power Source: 120VAC ~ 50/60 Hz ~ 35mA  
Output Power to Doorstrike: 16VAC - 15W  
Weight: 3 lbs.  
Operating Environment: 41° F - 95 ° F

Ring Generator: 7 REN maximum  
Relay contact ratings: 3A @ 250VAC  
Size: **W** 7.187 in. x **H** 10.125 in. x **D** 2.031 in.  
Patented by United States Patent & Trademark Office