

Ennovah Q-26/DP

Remote Door Entry Control & Monitoring

Operating Features

Basic Features

Doorphone-to-handset intercom with standard phone sets:
corded, cordless or multi-handset.
Door intercom running on inside phone wirelines.
Door intercom with or without dial tone service from telco.
Remote door release with keystroke on telephone keypad.
Call waiting at door call while phone conversation ongoing.
Call waiting at incoming phone call during entry intercom conversation.
Door answering by Answering Machine while residents are away as desired.

Advanced Features

Doorphone call forwarding to remote phone number or cell phone as desired.
Alarm security alert relayed to same or distinct remote phone number or cell phone as desired.
Programmable dial out mode and numbers from any home handset.
Door release capability for both failsafe and failsecure doorstrike and deadbolt on one port.
Operates with doorphone at 5 miles away from main location.
Full duplex doorphone communication with commercial-grade volume.
Built-in capability for duplex residence with 2-unit Doorphone (requires IPX or IPC expansion card)
Outdoor tamper monitoring from doorphone.
Leave or arrival alerts and communication with guests from hybrid doorphone/alarm port.
Environmental, safety and intrusion surveillance from one independent alarm port.
Door/gate entry surveillance with phone ring alerts.
Door/gate entry surveillance with both phone ring alerts and Doorchime alerts.
Call parking with timeout alert.
Music on Hold or custom message to remote subscriber line caller put on hold.
Selectable incoming phone call alerts by Doorchime box.
Control of video monitors with dedicated video control port.
Expandable to 4 doorphones with built-in expansion slot (requires DPX expansion card).
Secure control cabinet with inside cable management fixtures.
Integrates with Apartment Building Door Entry System (OmniCom 64).

Optional Features

Keyless entry access with Code Access Keypad or encrypted Keychain remote.
Large variety of doorphone models: from entry-level thin-metal pieces to vandal-proof doorphones.
Video surveillance with stealth micro camera within doorphone and standard TV set or LCD screen.
Video processing for delivery of capture screen to several TV's with optional video expansion slot.*
Video surveillance with universal stand-alone (indoor or outdoor) cameras.*
Video surveillance with both stealth doorphone micro cameras and stand-alone cameras.*
Video Monitoring with either dedicated TV receptor, LCD screen or Computer Monitor.
Video Monitoring with existing home TV sets, LCD screen and Computer Monitor simultaneously.*
Video surveillance with video doorphone at 1000 ft. away from premise (requires mini amplifier).
Integration with Picture-in-Picture TV sets for guest's picture on pop up mini window over main screen.
Integration of video doorphones with other video surveillance systems.
Upgradable to include room-to-room intercom and room-to-room call transfer.
Interoperable with other vendor's wholehouse audio system.
Optional CAT5 cabling for video doorphones or cameras (requires baluns).
Keychain remote to arm and disarm alarm detectors on hybrid port.

Installation & Interoperability

Self-test routines to support installation process.
Selectable installation modes: line intercept or plug and play.
Three on-board power supplies for alarm detectors, Access Keypad, doorstrikes and cameras.
Compatible with conventional PBX business phone systems and IP-based phone systems.
Compatible with KSU-less phone systems.



Technical Specifications

Preset Power Source:
115VAC ~ 50/60 Hz ~ 50mA
or 230VAC ~ 50/60 Hz ~ 50mA
On-board power supplies:
12VDC regulated - 24V DC unregulated - 18VAC
Resettable protection on 24VDC and 18VAC supplies
Weight: 5 lbs.
Operating Environment: 10° F - 95° F
Intercom Mode: Full-Duplex
Ring Generator: 7 REN maximum
Doorchime Relay contact ratings:
5A @ 24V DC or AC
Doorstrike Relay contact rating:
5A @ 24V DC or AC
Phone-to-chime enabling switch
(minimum rating): 10mA @ 5V DC
Premise wiring: CAT5 - preferably **shielded** in large homes (over 2000 sq ft.)
Cabinet size:
W 11 in. x **H** 12 in. x **D** 3.5 in.
Product code: Q-26/DP
Patented by:
United States Patent & Trademark Office

All operating features and specifications subject to change without notice.
Copyright © Quantometrix, Inc., 2005 Rev.1.1
www.quantometrix.com - 1- 800-766-0266

* requires Video Processor expansion card (VIP)

Compatible with DSL phone lines delivered either with a line splitter or phone set filters.
Compatible with all answering machines.
Full caller ID pass-thru to handsets.
Automatic transfer of dial tone to all home phone sets in event of power outage.